



OXYGEN SCAVENGER CONCENTRATED NEUTRAL SULFITE

DESCRIPTION AND USE

OXYGEN SCAVENGER is a concentrated neutral pH sulfite solution designed to react with oxygen present in the boiler feedwater. By acting as an oxygen scavenger, the products are used to control corrosion and pitting caused by the presence of this dissolved gas.

CHEMICAL FEEDING AND CONTROL

OXYGEN SCAVENGER may be fed neat directly from the shipping container or can mixed in a chemical feed tank with most common chemicals used for treatment. Steel, stainless steel or plastic may be used in the feed system. Copper, copper alloys and aluminum must be avoided.

OXYGEN SCAVENGER is normally controlled by a sulfite test on the boiler water. Control ranges can vary widely depending upon both makeup water characteristics and system operating conditions and will be specified by the technical representative servicing the facility.

TYPICAL PROPERTIES

Appearance.....	Clear liquid
Odor.....	Trace, characteristic
Specific Gravity.....	1.20-1.22
Flash Point.....	None
pH (undiluted).....	6.5-7.5

SAFETY AND HANDLING

OXYGEN SCAVENGER may be toxic by ingestion. Do not take internally. If ingested, drink at least two (2) glasses of water and get medical attention. Contact with eyes causes irritation. If eyes are contacted, immediately flush with clear water for 15 minutes and if irritation persists, get medical attention. For skin contact, wash with soap and water. For additional information, see the Material Safety Data Sheet provided with this product.

PACKAGING

OXYGEN SCAVENGER is packaged in 55, 30 and 15 gallon non-returnable plastic drums. Other packaging available by request.