SECTION 1:	IDENTIFICATION
Company Name:	QUALICHEM TECHNOLOGIES
Åddress:	885 Woodstock Rd, Ste 430-111
	Roswell, GA 30075
Phone No.	(800) 658-7716
Fax No.	
Emergency Phone No.	CHEM-TEL 800-255-3924
Date Prepared:	12/11/08
Date Revised:	

SECTION	12:
---------	-----

MATERIAL	CAS NO.	<u>%</u>
CARBOXYLATED ACRYLIC COPOLYMERS AND TERPOLYMER	PROPRIETARY	< 20
ORGANOPHOSPHONATE	PROPRIETARY	< 10
SODIUM HYDROXIDE	1310-73-2	< 1
SODIUM MOLYBDATE	7631-95-0	< 1

SECTION 3:

HEALTH HAZARDS

Ingestion:	MAY BE TOXIC IN CONCENTRATED FORM. DO NOT TAKE INTERNALLY. DUE TO HIGH ALKALINITY, CAUSES SEVERE IRRITATION, POSSIBLE BURNS OF INTERNAL TISSUES.
Inhalation:	NOT A LIKELY ROUTE OF EXPOSURE. INHALATION OF MIST IRRITATING TO RESPIRATORY TRACT.
Skin Contact:	PROLONGED CONTACT CAUSES SEVERE IRRITATION.
Eye Contact:	CAUSES SEVERE IRRITATION, POSSIBLE BURNS AND EYE DAMAGE.
Other Information:	OTHER THAN ACUTE EFFECTS LISTED ABOVE, NO LONG TERM EFFECTS
	KNOWN.

SECTION 4:

FIRST AID

Ingestion:	DRINK SEVERAL GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GET MEDICAL ATTENTION.
Inhalation:	
	PERSIST.
Skin Contact:	WASH WITH PLAIN WATER OR SOAP AND WATER.
Eye Contact:	IMMEDIATELY FLUSH WITH CLEAR WATER FOR 15 MINUTES AND GET MEDICAL
	ATTENTION IF IRRITATION PERSISTS.
Notes to Physician:	NO ANTIDOTES KNOWN. TREAT SYMPTOMS SUPPORTIVELY.

SECTION 5:

FIRE AND EXPLOSION HAZARD DATA

Flash Point/Method:	NONE
Upper/Lower Limit in Air:	N.A./N.A.
Extinguishing Media:	WATER OR ANY MEDIA SUITABLE FOR THE SURROUNDING FIRE. FIRE-FIGHTERS
Procedures:	SHOULD WEAR NORMAL PROTECTIVE EQUIPMENT. SELF-CONTAINED
	BREATHING APPARATUS SHOULD BE USED INCONFINED AREAS.
Unusual Hazards:	NONE
Combustion Products:	IF WATER IS EVAPORATED, OXIDES OF CARBON AND PHOSPHORUS MAY BE
	PRODUCED.

SECTION 6:	ACCIDENTAL RELEASE MEASURES
Personal Precautions: Environmental Precautions:	WEAR PERSONAL PROTECTIVE EQUIPMENT AS RECOMMENDED IN SECTION 8. THIS PRODUCT HAS A MODERATE HAZARD POTENTIAL IF RELEASED INTO THE ENVIRONMENT ACCIDENTLY.
Procedures for Clean Up:	SMALL SPILLS MAY BE FLUSHED WITH COPIOUS QUANTITIES OF WATER, PREFERABLY TO A SANITARY SEWER. LARGER SPILLS MAY BE DIKED TO MINIMIZE RUN-OFF AND NEUTRALIZED WITH DILUTE ACID. LIQUID MAY BE ABSORBED IN SAWDUST OR ANY AVAILABLE ABSORBANT AND SWEEPINGS DISPOSED OF IN A LANDFILL. OBEY ALL FEDERAL, STATE OR LOCAL REGULATIONS.
Prohibited Materials:	NONE
SECTION 7:	HANDLING AND STORAGE
Handling:	THIS PRODUCT IS A STRONG ALKALINE MATERIAL AND THE WEARING OF INDICATED PROTECTIVE EQUIPMENT IS REQUIRED WHEN HANDLING THE UNDILUTED MATERIAL.
Storage:	KEEP OUT OF REACH OF CHILDREN. STORE IN A COOL, DRY PLACE. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE.
SECTION 8:	EXPOSURE CONTROLS/PERSONAL PROTECTION
Precautionary Measures:	STANDARD INDUSTRIAL HANDLING PRECAUTIONS. WASH THOROUGHLY AFTER HANDLING CHEMICALS.
Engineering Controls:	USE WITH ADEQUATE VENTILATION TO KEEP EXPOSURES BELOW OCCUPATIONAL EXPOSURE LIMITS.
Control Limits:	SODIUM HYDROXIDE: OSHA PEL: 2 mg/m ³ Ceiling; ACGIH TLV: 2 mg/m ³ Ceiling. SODIUM MOLYBDATE: OSHA PEL: 5 mg/m ³ FOR SOLUBLE MOLBYDENUM COMPOUNDS AS Mo.
Equipment for Personal Protection:	SAFETY GLASSES WITH SIDE SHIELDS, GOGGLES, OR FACESHIELD, IMPERMEABLE GLOVES, AND PROTECTIVE CLOTHING SHOULD BE WORN WHEN HANDLING THE CONCENTRATED PRODUCT. EYEWASH STATION IN AREA OF USE.

SECTION 9:	PHYSICAL AND CHEMICAL PROPERTIES
Appearance:	CLEAR LIQUID
Odor:	
pH (undiluted):	>12.5
Specific Gravity:	1.13-1.15
Density:	9.56 lbs./gal.
Solubility in Water:	COMPLETE
Boiling Point:	212°F
Percent Volatile:	>70 (WATER)
Vapor Pressure (mmHg):	N.D.
Vapor Density:	
Evaporation Rate:	(water=1): ~1

SECTION 10:

STABILITY AND REACTIVITY

Stability:	STABLE
Conditions to Avoid:	NONE
Hazardous Polymerization:	STABLE
Conditions to Avoid:	NONE
Incompatibility:	MAY REACT WITH STRONG OXIDIZING AGENTS OR ACIDS.
Hazardous Decomposition	
Products:	IF WATER EVAPORATED, OXIDES OF CARBON & PHOSPHORUS COULD BE
	PRODUCED BY COMBUSTION.

SECTION 11:	TOXICOLOGICAL INFORMATION
Material & Tests:	CARBOXYLATED ACRYLIC COPOLYMERS AND TERPOLYMER: ORAL LD50 - RAT: >380 mg/kg. ORGANOPHOSPHONATE: ORAL LD50 (MOUSE) 1800 mg/kg. SODIUM HYDROXIDE: IRRITATION DATA; SKIN (RABBIT) = 500 mg/24 H (SEVERE); EYE (RABBIT) = 50 ug/24H (SEVERE). SODIUM MOLYBDATE: ORAL LD50 (RAT) 4000 mg/kg, INHALATION LC50 (RAT) >2080 mg/m3/4 Hr.

SECTION 12:	ECOLOGICAL INFORMATION
Aquatic Toxicity:	CARBOXYLATED ACRYLIC COPOLYMERS AND TERPOLYMER: 96 HR. LC50 RAINBOW TROUT >1000 mg/l, 48 HR. EC50 DAPHNIA MAGNA >1000 mg/l. ORGANOPHOSPHONATE: RAINBOW TROUT (96 Hr LC50) 5300 mg/l, DAPHNIA MAGNA (48 Hr LC50) 300 mg/l. SODIUM HYDROXIDE: 48 HR LC50 BLUEGILL SUNFISH = 99 mg/l; 96 HR LC50 MOSQUITO FISH = 125 mg/l; 48 HR LC50 BROWN SHRIMP = 30 - 100 mg/l. SODIUM MOLYBDATE: 96 HR LC50 (STRIPED BASS) >79.8 mg/l; 96 WEEK EC50(AMPHIPOD) =2,650 mg/l.

SECTION 13:	DISPOSAL CONSIDERATIONS
General Considerations:	THIS PRODUCT HAS A SUFFICIENTLY HIGH ENOUGH pH TO BE CONSIDERED A CORROSIVE WASTE.
Procedures:	DISPOSAL BY USE PREFERRED BUT IF THIS NOT POSSIBLE, DILUTE WITH COPIOUS QUANTITIES OF WATER, NEUTRALIZE WITH DILUTE ACID AND FLUSH TO WASTE, PREFERABLY TO A SANITARY SEWER. HOWEVER, OBEY ALL FEDERAL, STATE OR LOCAL REGULATIONS.

SECTION 14:	TRANSPORT INFORMATION
Shipping Name:	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (SODIUM HYDROXIDE)
Primary Hazard Class:	8
Identification No.:	UN3266
Packing Group:	
2004 NAERG No.:	154

SECTION 15:

REGULATORY INFORMATION

<u>Regulation</u> CERCLA (40 CFR302.4):	<u>Material</u> SODIUM HYDROXIDE	<u>RQ</u> 1000 lbs.	<u>Max. %</u> 1.0			
SARA 302 (Sect. 355, Appendix A):	<u>Material</u> NONE	<u>TPQ</u>	<u>Max. %</u>			
SARA 311/312:	<u>Categories</u> IMMEDIATE HEALTH	Hazards EYE IRRITANT				
SARA 313 (40 CFR 372.45):	<u>Material</u> NONE		<u>Max. %</u>			
CWA (40 CFR 401.15):	NONE					
RCRA (40 CFR 261):	NONE					
OSHA (29 CFR 1910.1200):	ALL COMPONENTS LISTED UNDER THIS STANDARD ARE SHOWN IN SECTION 2 OF THIS MSDS.					
TSCA:	ALL INGREDIENTS IN THIS PRODUCT ARE LISTED IN THE TSCA INVENTORY.					

STATE INGREDIENT <u>%</u> REGULATORY DESIGNATION
--

NONE

SECTION 16 OTHER INFORMATION

SUGGESTED HAZARD RATINGS

<u>NFPA</u> *	HAZARD	HMIS*
2	HEALTH (Blue)	2
0	FIRE (Red)	0
0	REACTIVITY (Yellow)	0
	PERSONAL PROTECTION	D
	SPECIAL HAZARDS	

*Notes: 0 = Insignificant; 1 = Slight; 2 = Moderate; 3 = High; 4 = Extreme

The data contained in this Material Safety Data Sheet has been prepared based upon an evaluation of the ingredients in the product, their concentration in the product and potential interactions. The information is offered in good faith and is believed to be accurate. It is furnished to the customer who is urged to study it carefully to become aware of hazards, if any, in the storage, handling, use and disposal of the product; and to insure his employees are properly informed and advised of all safety precautions required. The information is furnished for compliance with the "Occupational Safety and Health Act" of 1970, the "Hazards Communication Act" of 1983 as well as various other Federal, State and Local regulations. Use or dissemination of all or part of this information for any other purpose is prohibited by law.