

CW1336 AIR WASHER TREATMENT

DESCRIPTION

CW1336 is a treatment program for air washer systems operating at moderately scaling conditions. The product contains a combination of phosphonates, polymeric dispersants, azole, and an organic surfactant. CW1336 is effective when used during summer (condensing) and winter (evaporating) operations. The product will provide corrosion, scale, and general fouling control as required in these systems. CW1336 contains a low level molybdenum tracer for controlling product concentration.

FEATURES AND BENEFITS

- Controls deposition and scale
- Effective during condensing and evaporating operation
- Molybdenum traced for ease of product feed control

PRODUCT FEED AND CONTROL

CW1336 is normally fed using a chemical metering pump or shot fed. The product is normally fed neat directly from the shipping container. Tanks, pumps, piping and valves should be made of stainless steel, polyethylene, or PVC.

Treatment control ranges vary depending on the make-up water characteristics and system operating conditions. CW1336 is controlled by a low range molybdenum test. The technical specialist servicing the facility will provide specific treatment control levels based on system conditions.

PHYSICAL PROPERTIES

Physical properties of CW1336 are shown on the Material Safety Data Sheet (MSDS), a copy of which is available upon request.

STORAGE AND HANDLING

Keep in a tightly closed container. Store indoors. Recommended storage temperature is 50° F - 105° F (10° C - 40° C). Do not reuse container. Dispose of empty container in compliance with federal, state/provincial and local laws and regulations.

ENVIRONMENTAL, HEALTH, AND SAFETY

For detailed information, consult the material safety data sheet (MSDS).

PACKAGING

CW1336 is available in a wide variety of customized containers and delivery methods.