

## **CW1354NM COOLING WATER TREATMENT FOR OPEN RECIRCULATING SYSTEMS**

### **DESCRIPTION**

CW1354NM is a treatment for open, recirculating cooling water systems that has been optimized for scale control. The product contains a combination of phosphonates, polymeric dispersants and azole specifically formulated to minimize scale, general deposition and corrosion under operating conditions prone to deposition.

### **FEATURES AND BENEFITS**

- Controls deposition and scale
- Reduces water and treatment cost by enabling higher cycle operation
- No acid feed required

### **PRODUCT FEED AND CONTROL**

CW1354NM is normally fed using a cooling tower chemical metering pump. The product is normally fed neat directly from the shipping container. Tanks, pumps, piping and valves should be made of stainless steel, polyethylene, or PVC.

Treatment control ranges vary depending on the make-up water characteristics and system operating conditions. CW1354NM is controlled by a polymer or phosphonate test. The technical specialist servicing the facility will provide specific treatment control levels based on system conditions.

### **PHYSICAL PROPERTIES**

Physical properties of CW1354NM are shown on the Material Safety Data Sheet (MSDS), a copy of which is available upon request.

### **STORAGE AND HANDLING**

Keep in a tightly closed container. Store indoors. Recommended storage temperature is 50° F - 105° F (10° C - 40° C). Do not reuse container. Dispose of empty container in compliance with federal, state/provincial and local laws and regulations.

### **ENVIRONMENTAL, HEALTH, AND SAFETY**

For detailed information, consult the material safety data sheet (MSDS).

### **PACKAGING**

CW1354NM is available in a wide variety of customized containers and delivery methods.